## **COMPLIANCE MATRIX**

Sl. No.					Specification	on			Vendor's response (Parameter value/Noted/Complied)	
1.0	Mild sto	eel eq								
		Sl. No.	Size in mm	Length i	n Material	Applicable Standard	Qty. (Nos.)	Approx. weight (kg)		
		1.1	ISA $25 \times 25 \times 0$			IS808: 2021	30	162		
		1.2	ISA $40 \times 40 \times 00$		— Mild stee	or any	30	315		
		1.3	ISA $50 \times 50 \times 00$			equivalent	30	405		
		1.4	ISA $65 \times 65 \times 00$	3000		standard	16	280		
2.0	Mild steel Beams.									
		SI. No.	Size in mm	Length in mm	Material	Applicable Standard	Qty. (Nos.)	Approx. weight (kg)		
		2.1	ISMB 100	3000		IS808: 2021 or	10	270		
		2.2	ISMB 125	3000	Mild steel	any equivalent	06	240		
		2.3	ISMB 150	3000		standard	06	270		
3.0	Mild steel Channels.									
		Sl. No.	Size in mm	Length in mm	Material	Applicable Standard	Qty. (Nos.)	Approx. weight (kg)		
		3.1	ISMC 75	3000	Mild steel	IS808: 2021 or any equivalent	06	129		
		3.2 ISMC 100 3000		standard	06	174				

4.0	Mild	steel Fl	lat.									
		Sl. No.	Size in mm	Length in	1 Materi	19 I 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	plicable andard		Qty. Nos.)	Approx. weight (kg)		
		4.1	ISF 25 × 03	3000					06	10.8		
		4.2	ISF 25 × 06	3000		IS173	0: 1989 o	r	06	21.6	1	
		4.3	ISF 40 × 03	3000	Mild ste	eel any e	quivalent	;	06	18		
		4.4	ISF 40 × 06	3000		sta	andard		06	36		
		4.5	ISF 50 × 06	3000					06	42		
5.0	Stainl	ess ste	el equal angles.									
		Sl. No.	Size in mm	Length in mm	Materia		icable dard	Qt (No	·	Approx. weight (kg)		
		5.1	L 25 × 25 × 05	3000	AISI	ASTM	´	10	)	54		
		5.2	L 40 × 40 × 06	3000	Stainless	2	any	10	)	105		
		5.3	L 50 × 50 × 06	3000	steel 304	1.   -	alent - dard	10	)	135		
6.0	Stainl	ess ste	el seamless pipes a	nd tubes.	1	<b>'</b>	<u> </u>		<u>l</u>			
		Sl. No.	Size in mr	n	Length in mm	Material	Applica Standa		Qty. (Nos.)	Approx. weight (kg)		
		6.1	1 ½" NPS SC	H10	3000		A CTI	. 1	02	19		
		6.2	1" NPS SCH	H10	3000	AISI	ASTN A312,		04	25.2		
		6.3	¾" NPS SCI	H10	3000	Stainless	any		04	16		
		6.4	½" NPS SCI	H10	3000	steel	equival		04	12		
		6.5	10mm (OD) x 8n	nm (ID)	3000	304L	standa		02	1.84		
		6.6	19mm (OD) x 151	mm (ID)	3000				08	20.4		

7.0 Stainless Steel Electric Resistance Welded (ERW) pipe
---

Sl. No.	Size in mm	Length in mm	Material	Applicable Standard	Qty. (Nos.)	Approx. weight (kg)
7.1	1 ½" NPS SCH10	3000			10	95
7.2	1" NPS SCH10	3000	AISI	ASTM A312, or any	10	63
7.3	<sup>3</sup> / <sub>4</sub> " NPS SCH10	3000	Stainless steel 304L	equivalent standard	06	24
7.4	½" NPS SCH10	3000		Surraura	06	18

## 8.0 Stainless steel and Aluminum sheets.

Sl. No.	Size Width × Length × Thickness (mm)	Sheet Type	Material	Qty. (Nos.)	Applicable Standard	Approx. weight (kg)
8.1	1250 × 2500 × 03	Chequered	AISI Stainless steel 304	03	IS 6911: 1992 or any equivalent standard	225
8.2	1220 × 2440 × 01	Plain	Aluminum Alloy 1100 ( Commerci al grade )	03	IS 737: 2008 or any equivalent standard	24

## 9.0 General terms and conditions

9.1 Mill test certificate for the stainless steel and aluminum raw material shall be provided along with the supply. If a Mill test certificate is not available, a material composition test certificate for the items

	from NABL accredited lab shall be provided along with the supply.	
9.2	The price shall be quoted on a "PER KG" basis. The quoted price shall be inclusive of test certificate	
	charges.	
9.3	The price shall be quoted on a "FOR URSC" basis.	
9.4	It is a full supply package. Hence, an offer for part supply will not be considered. The lowest offer [L-	
	1] will be decided based on the aggregate value of all items put together.	
9.5	The Lowest offer (L1) arrived weights, as mentioned u/s 1.0 to 8.0 will be taken as a reference for	
	arriving at L1 offer. However, the Vendor can supply the items with a weight tolerance of ±10% on	
	individual items and Payment will be made on the "Actual weight" supplied basis.	
9.6	The weight of the material shall be provided by the vendor in the offer as well as the supply invoice.	
9.7	The supplied items shall be free from cracks, rust, dents, scratches and burrs.	
9.8	Acceptance: Material will be accepted only after verifying the required dimensions and material	
	composition at URSC, Bangalore.	
9.9	Material shall be sourced from reputed Indian manufacturers. Vendor to provide the information of	
	manufacturer in the quote.	