| Compliance Matrix to be filled up by vendor | | | | |
|---|--|--|---------------------------------------|--|
| Sr. No. | Specification | Specification-Value | Specification-value offered by Vendor | Compliance by Vendor (in Yes/No format only) |
| | • | General Specification | S | |
| 1 | Supply | Vendor shall ensure safe delivery of the products along with necessary accessories. | | |
| 2 | Warranty | The products delivered shall have warranty of 1 year from the date of delivery. The warranty shall cover material/performance defects. | | |
| 3 | Evaluation Criteria | Indent of single Item, L1 basis | | |
| 4 | Confirmation of Compliance Matrix | Vendor is required to submit confirmation of compliance matrix at the time of submitting quote. (Blank document is attached along with indent) | | |
| 5 | Delivery Time | Products to be delivered within 6 weeks from release of PO | | |
| | Item: C | LEAN ROOM MATERIALS - Sterile | Garment Storage Cabin | et |
| 1 | Material | Stainless steel (SS 304) | | |
| 2 | Cleanliness Level | Class 1000 (ISO Class) or better | | |
| 3 | Airflow | Vertical or Horizontal recirculatory air flow with positive pressure, HEPA filter and blower assembly | | |
| 4 | High Efficiency Particulate Air - HEPA filter efficiency | 99.99% or better at 0.3 microns | | |
| 5 | Pre-filter efficiency | 75% or better at 5 microns | | |
| 6 | Shelving and Storage | Hanging Rods, Fixed shelves | | |
| 7 | Doors | Two-sided opening | | |
| 8 | Illumination | LED lighting | | |
| 9 | UV light | For additional disinfection, safety interlocking to prevent exposure when doors are opened | | |
| 10 | Differential Pressure Gauge | To check the pressure drop across HEPA filter | | |
| 11 | Blower motor assembly | Electric motor single phase | | |
| 12 | Power supply | 220V AC, 50Hz | | |
| 13 | Compatibility | Product should be functionally compatible with fully covered directions of left, right, back, top | | |
| 14 | Duct mounting available for Inlet & Outlet air flow | Front Only | | |
| 15 | Overall Width | 925mm (+/- 5mm) | | |
| 16 | Overall Depth | 550mm (+/- 50mm) | | |
| 17 | Overall Height | 1750mm (+/- 50mm) | | |