## **TECHNICAL**

## Tow

| S.No. | Parameter                                  |
|-------|--|
| 1     | Product Type                               |
| 2     | Resolution                                 |
| 3     | Bands                                      |
| 4     | Fresh Tasking/ Archive data                |
| 5     | Period of interest                         |
| 6     | Cloud% acceptable                          |
| 7     | Off Nadir Angle (ONA)                      |
| 8     | Delivery Media                             |
| 9     | Proj ection / Datum                        |
| 10    | Resampling Kernel                          |
| 11    | Format                                     |
| 12    | Bit Depth                                  |
| 13    | Tiling                                     |
| 14    | License                                    |
| 15    | Segment                                    |
| 16    | End application                            |
| 17    | Any other additional/Specific requirements |

## SPECIFICATIONS n: Kakching

| Description                                       |
|---|
| Town Mosaic Orthorectified , 4 Band Pan Sharpened |
| 0.40 m  |
| 4 Band Pan Sharpened                              |
| Fresh Tasking                                     |
| Within 3 months                                   |
| Cloudfree is preferable.                          |
| Zero% Cloudcover on builtup area, Less than 10%   |
| cloudcover in the other areas of AOI              |
| ≤ 15 deg  |
| USB   |
| UTM/WGS 84  |
| Nearest Neighbourf                                |
| Geotiff   |
| 10 bit or better                                  |
| NA  |
| Single  |
| Commercial  |
| Large Scale Mapping                               |
| 1. Planimetric Accuracy: 5m CE90                  |
| 2. Occlusion and distortion free data is required |