

Technical specifications of BNC Male to SMA Female Adapters			
Sr. no.	Parameter Description	Specification	Vendor's Compliance
1	Frequency range (minimum)	DC-2 GHz	
2	Insertion Loss (maximum)	0.5dB	
3	Impedance	50 ohm nominal	
4	Type	BNC Male- SMA Female	
5	Size: Length X Diameter(mm) ± 1mm	Less than 35 x 15 mm	
6	Temperature Range	-20 deg C to +75 deg C	
7	VSWR across the entire Frequency Band (Maximum)	1.3:1	
8	No. of Matings (Minimum)	500	
9	Voltage handling (Minimum)	250V	
10	Orientation	Straight	
11	Center Contact	Beryllium copper gold plated or brass gold plated	
12	Connector Body Material	Passivated stainless steel or Brass body nickel/gold plated	
13	Insulator	PTFE	
14	Warranty Product offered shall carry min. one year warranty against any manufacturing defects		
15	Terms & Conditions <ol style="list-style-type: none"> I. Only OEM / Authorized representative of OEM is allowed to quote for this bid. Authorization certificate should be provided. II. All the parts shall be packed individually and each bag shall be marked. III. Vendor shall mandatorily provide the following documents along with bid, failing which the quote is liable to be rejected. <ol style="list-style-type: none"> a. VSWR plot over frequency range b. Attenuation over Frequency range c. Datasheet mentioning all the compliance d. Mechanical Drawing IV. Vendor should provide COC and Warranty certificate along with the supply of materials. V. Tentative drawing only for illustration purpose, indicating the type of adaptor. 		

