

Specifications

Annexure

Note : Dimension tolerance +/- 10mm is acceptable

1. ESD molded conductive crates with Lid & Lock (SI No 1-3)

	Description	Specification
1	Material	Conductive Polypropylene
2	Electrical properties	10^3 to 10^7 Ohms/Sq approx preferable
3	Load Capacity	<ul style="list-style-type: none">• 400 x 300 x 320mm (7-10Kg)• 600 x 400 x 325mm (15-20Kg)• 300 x 200 x 150mm (1-3Kg)
4	Color	Black preferred
5	Handles required at both sides for holding the box	

2. ESD safe corrugated boxes with lid & lock (SI No.4-7)

SI No	Description	Specification
1	Material	5mm thick Conductive (permanent) polypropylene corrugated sheet
2	Surface Resistivity	10^4 to 10^6 Ohms/Sq approx. preferable
3	Load Capacity	<ul style="list-style-type: none">• 400 x 200 x 50 mm (1-3Kg)• 400 x 400 x 50 mm (3-5Kg)• 200 x 200 x 50mm (1-2Kg)• 100 x 100 x 50 mm (0.5-1kg)
4	Color	Black preferred
5	Handles preferred at both sides for holding the box	

General terms & condition

- Photograph or catalogue for quoted item should be submitted along with the offer.
- Item should be properly packed as per standard packing norms.
- Item may be preferably delivered within 4 to 8 weeks after receipt of P.O.